

## Datasheet AHF-BW

### Composition

Fabric	: Cotton jersey	80 gr/m <sup>2</sup>
Coating	: Plasticized PVC/PVC foam, flame retardant	<u>510 gr/m<sup>2</sup></u>
Thickness	: 1,10 mm ±	590 gr/m <sup>2</sup> ± 7.5%

### Properties

		Length	Width	
Tensile strength	DIN53354	300 N/5cm	220 N/5cm	± 20 %
Elongation	DIN53354	40 %	185 %	± 25 %
Tear strength	DIN53356	15 N	15 N	± 35 %
Adhesion	DIN53357	> 50 N/5cm		
Impermeability to water	DIN53886	> 100 cm		
Colorfastness	ISO 105	> 6		

Flame retardancy: FMVSS 302 (= 95/28/EG IV, R118) b, EN1021 1+2

### Special properties

The material meets the requirements for upholstery of seats of motor vehicles as stated in the Directive 95/28/EC (R118) of the European Parliament.

### Washing instructions



Clean with damp piece of cloth and household soap (solvent free).  
 Don't fold and put the material away when wet.

### Remarks

Small differences in color and gloss are possible (hold recipe numbers separated).  
 Reproducibility Color: unicolor < 1, printed < 1.5, dualcolor < 2 (Delta E CIE-lab 1976 D65).

Date: 26/9/2018

Datasheet date: 18/9/2008

ABN AMRO BANK: 47.37.10.978  
 IBAN: NL94ABNA0473710978  
 BIC: ABNANL2A

ING BANK: 903250  
 IBAN: NL45INGB0000903250  
 BIC: INGBNL2A

BTW/VAT: NL005840247B01  
 Chamber of Commerce: 08036741

Our general terms and conditions are applied to all our offers, orders and agreements. A copy is available on request.

