

Datasheet BKA

Composition

Fabric	: Polyester fabric, 1100 dTex, 7/7,5/cm	160 gr/m ²
Coating	: Double-sided, plasticized PVC, flame retardant	<u>260 gr/m²</u>
Thickness	: 0,37 mm ±	420 gr/m ² ± 7.5%

Properties

		Length	Width	
Tensile strength	DIN53354	2000 N/5cm	1900 N/5cm	± 20 %
Elongation	DIN53354	25 %	25 %	± 25 %
Tear strength	DIN53356	240 N	240 N	± 25 %
Adhesion	DIN53357	> 50 N/5cm		
Impermeability to water	DIN53886	> 100 cm		
Colorfastness	ISO 105	>= 7		
Cold resistance	DIN53361	< -25 °C		
Flame retardancy: EN1021 1+2				

Washing instructions



Handwash

Clean with damp piece of cloth and household soap (solvent free).

Don't fold and put the material away when wet.

Remarks

Small differences in color and gloss are possible (hold recipe numbers separated).

Reproducibility Color: unicolor < 1, printed < 1.5, dualcolor < 2 (Delta E CIE-lab 1976 D65).

Date: 26/9/2018

Datasheet date: 5/11/2014

ABN AMRO BANK: 47.37.10.978

IBAN: NL94ABNA0473710978

BIC: ABNANL2A

ING BANK: 903250

IBAN: NL45INGB0000903250

BIC: INGBNL2A

BTW/VAT: NL005840247B01

Chamber of Commerce: 08036741

Our general terms and conditions are applied to all our offers, orders and agreements. A copy is available on request.



Management
System
ISO 9001:2015

www.tuv.com
ID 9108622561